

TCB

**GRANT OF EQUIPMENT
AUTHORIZATION**

TCB

**Certification
Issued Under the Authority of the
Federal Communications Commission
By:**

**Timco Engineering, Inc.
849 NW State Road 45
Newberry, FL 32669**

**Date of Grant: 06/05/2019
Application Dated: 06/05/2019**

**WIRELESS-TAG TECHNOLOGY CO., LIMITED
Room 115-118, Building A, Chengshishanhai
Center, No. 11, Zhongxing Road, Bantian
Sub-District, Longgang district, Shenzhen, 518000
China**

Attention: Louie Wang , Manager

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: 2AFOS-WT-01F
Name of Grantee: WIRELESS-TAG TECHNOLOGY CO., LIMITED
Equipment Class: Digital Transmission System
Notes: WiFi module
Modular Type: Single Modular

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	15C	2412.0 - 2462.0	0.0719		

Single Modular Transmitter. Power output is conducted. Approval is limited to OEM installation only. Compliance of this device in all final host configurations is the responsibility of the Grantee. This device is to be used only for mobile and fixed applications. The antenna(s) used for this transmitter must not exceed the gain of 2.5 dBi and must be installed to provide a separation distance of at least 20cm from all persons, and must not transmit simultaneously with any other antenna or transmitter. OEM integrators must be provided with antenna installation instructions and labeling requirements for finished products. OEM integrators and end-Users must be provided with transmitter operation conditions for satisfying RF exposure compliance. This grant is valid only when the device is sold to OEM integrators and the OEM integrators are instructed to ensure that the end user has no manual instructions to remove or install the device. Separate approval is required for all other operating configurations, including portable configurations with respect to 2.1093 and different antenna configurations. This device has 20MHz bandwidth only.

